

## LED 155 EX



Offshore Lantern LED 155EX is a LED lantern commonly used on offshore platforms. The lantern is maintenance free, compact and robust in design. LED 155EX is modular and can be delivered with up to 3 tiers. LED 155EX is also available as a general purpose lantern for marking of obstacles. This version complies with ICAO Annex 14, Volume 1 and it can be configured with two different standard intensities depending on operational requirements.

[Contact Us](#) [Get a quote](#)

Rating: Not Rated Yet

[Ask a question about this product](#)

Description

### [Features](#)

#### **Offshore Lantern LED 155 EX features:**

- Range up to 8 NM at Tc = 0.74 (12 NM at Tc = 0.85)
- ATEX category Zone 1 and Zone 2
- Standard IALA colours Red, Green, White and Yellow
- Rugged aluminium housing
- Extremely low power consumption, suitable for solar and battery operation
- Integrated flasher with a daylight switch and an 8 A solar panel charger

- Adjustable intensity and range
- Available with narrow (6°) or wide (10°) vertical divergence
- Cable synchronization between light units

## [Downloads](#)

### **Downloads**

[\\_pdf Product Datasheet LED155EX \(pdf eng\) \(3.08 MB\)](#)

[\\_pdf Product Datasheet LED155EX \(pdf ES\) \(3.80 MB\)](#)

## [Extranet login](#)

### **Extranet login**

Remember Me

Log in [Create an account](#)

- [Forgot your username?](#)
- [Forgot your password?](#)